

Smart Lock Ultra & Nuki Universal Cylinder: Technical Specifications

Nuki Smart Lock Ultra	
Color	Stainless steel body with black and white base rings
Weight	250g
Dimensions	ø57 x 58 mm
Power supply	Lithium Polymer Battery
Communication	Bluetooth Low Energy: IEEE 802.15.1; 2,4GHz ISM band Antenna: internal RF ceramic chip antenna Frequency range: 2402MHz - 2480MHz Max. transmission power: 10 dBm (10 mW) Thread: IEEE 802.15.4; 2.4GHz ISM band, Antenna: internal RF ceramic chip antenna Frequency range: 2405MHz - 2480MHz Thread Max. transmission power: 10 dBm (10 mW) WLAN: IEEE 802.11 b/g/n 2,4 GHz WLAN antenna: 2.4 GHz ceramic antenna WLAN frequency range: 2412 MHz - 2484 MHz WLAN max. transmission power: 17 dBm (50 mW)
Operating temperature	10 - 40°C
Requirements	We recommend using Nuki products with the latest versions of iOS, Android or EMUI (Huawei)
Nuki Universal Cylinder	
Material	Stainless steel
Weight	250g
Dimensions	130 x 33 x 17 mm



Security	Security class SKG***
Shipment	
Shipment	● 1x Nuki Smart Lock Ultra ● 2x Rings (black & white) ● 1x Universal Cylinder ○ 1x Cylinder ○ Modular extensions ■ 30 mm - 55 mm modular extensions (outside) ■ 30 mm - 67,5 mm modular extensions (inside) ○ Carbide-Rods in 5 different lengths to adapt to outside extensions ○ Mounting screws for modular segments (inside) ○ Adapter ○ 3x keys ○ Security Card ○ Measurement Card ● 1x Mounting plate ● 1x Instructions ● 1x Allen wrench ● 1x Charging cable (USB-C) 2m